

## Gas Tool Fasteners

*(Pre-assembled, Sing-Shot)*

*The fasteners are designed for use in Ramset Single-Shot Gas Tools (R150, T3SS)*

*For suspended ceilings, piping and other items using 1/4" or 3/8" threaded rod. Fastener is pre-assembled to a 16 gage threaded rod hanger. 100 per jar.*

### THREADED ROD HANGER



#### PART

#### NUMBER

#### DESCRIPTION

#### R150

#### T3SS

14TRHMP034

1/4" Rod hanger with 3/4" plated pin



38TRHMP034

3/8" Rod hanger with 3/4" plated pin



Shank diameter = .104/.125 Head diameter = .300



*Used to attach conduit or armored cable to concrete. Fastener pre-assembled to a 16 gage conduit strap. 100 per jar, 3/8" 200 per jar.*

### ONE HOLE STRAP



#### PART

#### NUMBER

#### DESCRIPTION

#### R150

#### T3SS

38HSMP034\*

3/8" Hole strap with 3/4" plated pin (UL)



12HSMP034

1/2" Hole strap with 3/4" plated pin



34HSMP034

3/4" Hole strap with 3/4" plated pin



10HSMP034

1" Hole strap with 3/4" plated pin



Shank diameter = .104/.125 Head diameter = .300

\* 38HSMP034 = 18 gage

*Used to attach conduit to concrete. Pin pre-assembled to an 18 gage conduit strap. 1/2" 50 per jar and 3/4" 25 per jar.*

### CONDUIT CLAMP



#### PART

#### NUMBER

#### DESCRIPTION

#### R150

#### T3SS

12CCMP034L

1/2" Conduit clamp with 3/4" plated pin



34CCMP034L

3/4" Conduit clamp with 3/4" plated pin



Shank diameter = .104/.125 Head diameter = .300



CEILING CLIP ASSEMBLY

Pre-assembled Ceiling Clip.  
Plated 14 gage clip. 100 per jar.



PART NUMBER	DESCRIPTION	R150	T3SS
34CLIP	3/4" wide angle clip w/ 3/4" length pin	■	■

Shank diameter = .104/.125 Head diameter = .300

Used to install temporary lighting and secure low voltage cable to concrete, uses a standard cable tie up to 3/8" in width. Fastener is pre-assembled to a 22 gage tie strap holder. 50 per jar.

TIE STRAP HOLDER




PART NUMBER	DESCRIPTION	R150	T3SS
TSHMP034	Tie strap holder with 3/4" plated pin	■	■

Shank diameter = .104/.125 Head diameter = .300

MECHANICAL PIN WITH WASHER

Used for the attachment of light gage metal to concrete and steel such as HVAC duct strap to concrete. Plated pin pre-assembled to a 1/2" domed washer. 200 per jar, 1" 100 per jar.



MUST USE WITH  
MAGNETIC WORK  
CONTACT ELEMENT  
(M150200)

PART NUMBER	DESCRIPTION	R150*	T3SS*
M012	1/2" Plated step pin with domed washer	■	■
M034	3/4" Plated pin with domed washer	■	■
M034BB	3/4" Premium step pin with domed washer	■	■
M100	1" Plated pin with domed washer	■	■

Shank diameter = .125 Step Pin .104/.118  
Head diameter = .300 (M012=.250)  
\*Will fit R150 & T3SS with optional work contact element P/N M150200

1/4-20 THREADED STUD

Used to attach electrical components to concrete where removability of the component is required. Plated threaded stud. 200 per jar.



PART NUMBER	THREAD LENGTH	SHANK LENGTH	R150	T3SS
14STUD	1/2"	5/8"	■	■

Shank diameter = .125

Used for general purpose fastening to concrete. Plated pin with top hat.

TOP HAT PIN

200 per jar.



PART NUMBER	DESCRIPTION	R150	T3SS
MP034TH	3/4" Plated pin with top hat	■	■
Shank diameter = .125 Head diameter = .300			

BRIDLE RING

Pre-Assembled 2" Bridle Ring supports low voltage, data com, signal, and control cables 50 per box.



PART NUMBER	DESCRIPTION	T3SS
BR2	2" bridle ring	■
Shank diameter = .125		